United States Patent [19]

Semp et al.

[11] Patent Number: 4,895,603

[45] Date of Patent: Jan. 23, 1990

[54] APPARATUS AND METHOD FOR IN-PLACE CLEANING AND PRIMING OF A NOZZLE ASSEMBLY

[75] Inventors: Bernard A. Semp; Bernard C. Kiernan; David L. Bilunas; Michael L. Watkins, all of Richmond, Va.

[73] Assignee: Philip Morris Incorporated, New York, N.Y.

[21] Appl. No.: 286,354

[22] Filed: Dec. 19, 1988

[51] Int. Cl.[4] B08B 3/08; B08B 5/04

[52] U.S. Cl. ..... 134/21; 134/22.18; 134/22.19; 134/22.12; 134/22.14; 134/57 R; 134/169 R

[58] Field of Search ..... 134/21, 22.18, 22.19, 134/104.1, 198, 169 R, 22.12, 22.14

[56] References Cited

U.S. PATENT DOCUMENTS

3,146,950	9/1964	Lancaster	239/128
3,435,834	4/1969	Cooper	134/169 R
4,365,585	12/1982	Naylor et al.	118/302
4,420,635	12/1983	Washington et al.	562/555
4,500,770	2/1985	Vock et al.	219/121.7
4,562,099	12/1985	Hinchcliffe	427/282
4,763,672	8/1988	Gregory, III	131/79

FOREIGN PATENT DOCUMENTS

0072377	6/1978	Japan .
1314276	4/1973	United Kingdom .
2030894	4/1980	United Kingdom .
2163528	2/1986	United Kingdom .

OTHER PUBLICATIONS

"New Developments in CIP Practices", Chemical Engineering Progress, Jan. 1985, pp. 39–41.

Primary Examiner—Asok Pal
Assistant Examiner—Ourmazd Ojan
Attorney, Agent, or Firm—Charles B. Smith; Alan D. Smith

[57] ABSTRACT

An apparatus and method for in-place cleaning and priming of an in-place nozzle assembly which in normal operation receives from a reservoir and discharges to a work area a fluid material which tends to leave behind an accumulation of undesired residue. The apparatus includes control means for sequentially actuating for a selected cleaning time period first selectively actuatable means thereby to deliver an effective quantity of the cleaning substance to the nozzle and for actuating for a selected rinsing time period second selectively actuatable means thereby to deliver an effective quantity of the rinsing substance to the nozzle. The apparatus also includes third selectively actuatable means for drawing fluid material from the reservoir and delivering the same to the nozzle for a selected priming time period first to flush out any remaining rinsing substance from the nozzle and then to leave the nozzle primed with the fluid material.

2 Claims, 1 Drawing Sheet



2026230384

Source: https://www.industrydocuments.ucsf.edu/docs/mfjl0000